

AGC

CE Marking of Laminated glass – EN 14449
 Declaration of performances
 Stratobel clear (44.x, 55.x)

CE

We

AGC Flat Glass Europe
Division Raw Glass Products
 Chaussée de La Hulpe 166 - B 1170 Brussels
 Tel.: + 32 - (0) 2 674.31.11 - Fax: + 32 - (0) 2 674.44.62

Declare, under his sole responsibility, the following characteristics for the CE Marking of the glass products named **STRATOBEL**, intended to be used in buildings and construction works, following **EN 14449**

Stratobel characteristics in :	44.1	44.2	44.4	44.6	55.1	55.2	55.4
1. Resistance to fire (EN 13501-2)	NPD	NPD	NPD	NPD	NPD	NPD	NPD
2. Reaction to fire (EN 13501-1)	NPD	NPD	NPD	NPD	NPD	NPD	NPD
3. External fire performances	NPD	NPD	NPD	NPD	NPD	NPD	NPD
4. Bullet resistance (EN 1063)	NPD	NPD	NPD	NPD	NPD	NPD	NPD
5. Explosion resistance (EN 13541)	NPD	NPD	NPD	NPD	NPD	NPD	NPD
6. Burglar resistance (EN 356)	NPD	P1A-P2A	P3A-P4A	P5A	NPD	P1A-P2A	P3A-P4A
7. Pendulum body impact resistance (EN 12600)	2B2	1B1	1B1	1B1	1B1	1B1	1B1
8. Resistance against sudden temperature change and temperature differentials	NPD	NPD	NPD	NPD	NPD	NPD	NPD
9. Wind, snow, permanent and imposed load resistance	NPD	NPD	NPD	NPD	NPD	NPD	NPD
10. Direct airborne sound reduction (EN 12758): $R_w(C, C_{tr})$	34 (-1, -2)	35 (-1, -3)	NPD	35 (-1, -3)	35 (-1, -3)	NPD	36 (-1, -4)
11. Thermal properties:							
- U-value (EN 673)	5,6	5,6	5,5	5,3	5,6	5,5	5,4
- Normal emissivity ϵ_n (EN 12898)	0,89	0,89	0,89	0,89	0,89	0,89	0,89
12. Light transmission/reflection (EN 410): $\tau_v / \rho_v / \rho'_v$	88 / 8 / 8	88 / 8 / 8	88 / 8 / 8	88 / 8 / 8	87 / 8 / 8	87 / 8 / 8	87 / 8 / 8
13. Solar energy transmission/reflection (EN 410): $\tau_e / \rho_e / \rho'_e$	73 / 7 / 7	72 / 7 / 7	70 / 7 / 7	69 / 7 / 7	70 / 7 / 7	69 / 7 / 7	67 / 7 / 7

Brussels
 23rd of April 2008


 A. Jardinet
 Vice-President, Sales & Marketing Raw Glass Division